

PRODUCT TECHNICAL DATASHEET

BI/006

Brushless 

Intensive use 

Digital Encoder 




| CODE | DESCRIPTION | PCS/PALLET |
|--------|--|------------|
| BI/006 | Barrier BRUSHLESS 36V DC for booms up to 6 m, with control unit and absolute encoder, irreversible, complete with xing plate with tie rods, boom fixing angles and flashing white LED light on header. | 6 |

| PRODUCT TECHNICAL SPECIFICATIONS | |
|----------------------------------|--|
| Barriers | Up to 6 mt long |
| Power line supply | 230V AC - 50Hz |
| Motor power supply | 36V DC |
| Power rating | 220W |
| Frequency of use | Super intensive use |
| Torque | 10 - 300 N m |
| Operating temperature | - 20 + 55 C° |
| Protection level | IP54 |
| Reductor Type | Irreversible |
| Opening time | 4 ÷ 8 (sec) |
| Onboard control unit | CTRL |
| Encoder | Digital native encoder + magnetic digital SENSORED, 4096 PPR |
| Accessories power supply | 24V DC |
| Colour | Cabinet: painted RAL9006 arabesque grey - Head: black arabesque silver painted - Boom support: black arabesque silver painted - Boom: painted RAL9010 matt |
| Release system | European Key cylinder |
| Batteries recovery | Available (optional) |

| | |
|---|------------------|
| BUS synchronization Master/Slave | Yes |
| Operating cycles per day (opening/closing - 24 hours no stop) | 4000 |
| Maximum dimension product in mm (L x W x H) | 380 x 270 x 1237 |
| Product weight packed (Kg) | 75,1 |
| Number items per pallet/box | 6 |

PRODUCT DIMENSIONS AND PREPARING FOR INSTALLATION



DIMENSIONS

PRODUCT ACCESSORIES

| | | | | | |
|--|--|--|--|--|---|
| | | | | | |
| SP/83/01 Spring diameter 83 mm for barriers. | SP/85/01 Spring diameter 85 mm for barriers. | BA/90/2 White painted aluminum rod, 2 meters long, with LED cover profile and impact resisting rubber profile. | BA/91/3 White painted aluminum boom, 3 meters long, with LED cover profile and impact resisting rubber profile. | BA/91/4 White painted aluminum boom, 4 meters long, with LED cover profile and impact resisting rubber profile. | BA/91/6 White painted aluminum boom, 6 meters long, with LED cover profile and impact resisting rubber profile. |
| | | | | | |
| JNT/BA/91 Internal connection joint, anodised aluminium, with fixing screws for BA/91 booms. | BARK/02 Painted aluminum skirting, with stainless steel screws mounted on bronze bushings. Single module length 2 meters. | ALED/6C 6-metre LED strip with connection cable for barrier boom (red colour). | ALED/6C/RGB 6-metre multicoloured RGB LED (red, green + other colours) strip with connection cable for barrier boom. | BI/BLED/6/RGB Multicoloured RGB LED strip (red, green + other colours) with connection cable for BI/004HP - BI/006 barrier header. | BAFS/01 Fixed support with rubber, not adjustable, for booms. |
| | | | | | |
| BAFS/02 Fixed support with rubber, adjustable telescoping, for booms. | BAFS/03 Fixed support with rubber, not adjustable, with predisposition for bolt, for booms. | BAFS/04 Fixed support with rubber, adjustable telescoping, with predisposition for bolt, for booms. | BAFS/05 Adjustable fixed support with vandal-proof magnetic suction cup, complete with B72/DGS demagnetizer card, for booms. | BAMS/01 Mobile support for bars. | BAMS/01/EXT Extension 20 cm for mobile support BAMS/01. |
| | | | | | |
| BI/BAT/KIT Kit for emergency batteries charger for Brushless digital controller CTRL 36V DC with plug-in card, with 2 recovery batteries 12V DC, 4.5 Ah. Kit for BIONIK barrier. | BI/BCHP Plug-in card, batteries charger, for Brushless digital controller CTRL 36V DC, without recovery batteries, for BIONIK barrier. | BT12V45 Battery 12V 4.5 Ah (1 pc). | CRA/BAR Column for photocells G90/F2ES - G90/F4ES for spaced installation on a barrier cabinet (+23 cm). | CRA/BAR/M90 Column for photocells M90/F4ESO - M90/F4ESO for spaced installation on a barrier cabinet (+23 cm). | KT231 Fixing plate for fixed supports codes BAFS/01, BAFS/02, BAFS/03, BAFS/04, BAFS/05. |
| | | | | | |
| B73/EXP Signal status board, 2 output for CTRL - CTRL/P. | B73/LTM RGB boom light and traffic light control device for CTRL. | DLD1/24 Loop detector for 1 loop, 2 output, 24V AC/DC. | DLD2/24 Loop detector for 2 loops, 2 outputs + output alarm, 24V AC/DC. | KT239 Kit DIN rail with magnetic supports. | KT242 Kit for cable passage with magnetic support for barriers. |



R99/BASB20

Pack of 20 reflective adhesive stickers
for boom barrier.



R99/BASB40

Pack of 40 stickers for barrier.